

www.OVISION.com

tarif QSI

OPTIQUE&VISION

6 avenue de l'esterel 06160 JUAN LES PINS France tel 04 93 61 18 83 fax 04 92 93 09 83

2012 en cours

toutes nos cameras QSI sont livrées avec Prism Light V8

référence	description	€ HT	€ TTC
SERIE 583	Full-frame 8.3 megapixel KAF-8300 sensor, Low noise, wide dynamic range, 16-bit output, USB 2.0 Up to 45°C CC D cooling, Built-in mechanical shutter ,Maxlm DL and CCDSOft Drivers, Prism Light V8 software ,ASCOM-compatible Windows COM API, Linux drivers and API.		
583s	mechanical shutter	2772	3316
583ws	mechanical shutter + filter wheel	2963	3543
583wsg	mechanical shutter + filter wheel + internal guide port for autoguiding	3304	3952
SERIE 683	Full-frame 8.3 megapixel KAF-8300 sensor, Low noise, wide dynamic range, 16-bit output, fast USB 2.0, Up to 50°C CCD cooling, Built-in mechanical shutter, Maxlm DL and CCDSOft Drivers, Prism V8 light software ,ASCOM-compatible Windows COM API, Linux drivers and API, fast donwload, Prism V8 light offert.		
683s	mechanical shutter	3212	3841
683ws	mechanical shutter + 5 positions filter wheel	3402	4069
683ws8	mechanical shutter + 8 positions filter wheel	3694	4419
683wsg	mechanical shutter + five positions filter wheel + internal guide port	3694	4419
683wsg8	mechanical shutter + 8 positions filter wheel + internal guide port	3987	4769
SERIE 540	4.2mp 2048x2048 KAI-04022 sensor, Low noise, wide dynamic range, Very fast electronic shutter, Up to 45°C CCD cooling, Maxlm DL and CCDSOft Drivers, Prism Light V8 software camera control and image processing software ,ASCOM-compatible Windows COM API, Linux drivers and API		
540i	Very fast electronic shutter	3748	4483
540s	Very fast electronic shutter + Mechanical shutter	3846	4599
540ws	Very fast electronic shutter + Mechanical shutter + 5 positions filter wheel + internal guide port	3987	4769
540wsg	Very fast electronic shutter + Mechanical shutter + 5 positions filter wheel	4329	5177

SERIE 640	4.2mp 2048x2048 KAI-04022 sensor, Low noise, wide dynamic range, Very fast electronic shutter, Up to 50°C CCD cooling, MaxIm DL and CCDSoft Drivers, PRISM V8 light software ,ASCOM-compatible Windows COM API, Linux drivers and API		
640 i	Very fast electronic shutter	4041	4833
640s	Very fast electronic shutter + Mechanical shutter	4138	4949
640ws	Very fast electronic shutter + Mechanical shutter + 5 positions filter wheel	4329	5177
640ws8	Very fast electronic shutter + Mechanical shutter + 8 positions filter wheel	4621	5527
640wsg	Very fast electronic shutter + Mechanical shutter + 5 positions filter wheel + internal guide port	4670	5585
640wsg8	Very fast electronic shutter + Mechanical shutter + 8 positions filter wheel + internal guide port	4963	5935
SERIE 532	Full-frame 3.2 megapixel KAF-3200 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, PRISM Light V8 control and image processing software, CCDSoft and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.		
532s	Mechanical shutter	5553	6641
532ws	Mechanical shutter + 5 positions filters wheel	5694	6811
532wsg	Mechanical shutter + 5 positions filters wheel + internal guide port	6036	7219
SERIE 632	Full-frame 3.2 megapixel KAF-3200 sensor Low noise, Low noise, wide dynamic range, 16-bit output, Fast USB 2.0 Up to 50°C CCD cooling, Built-in mechanical shutter, MaxIm DL and CCDSoft Drivers, Prism V8 light software ,ASCOM-compatible Windows COM API, Linux drivers and API, fast download, Prism V8 light offert.		
632s	Mechanical shutter	5894	7050
632ws	Mechanical shutter + 5 position filter wheel	6036	7219
632ws8	Mechanical shutter + 8 position filter wheel	6329	7569
632wsg	Mechanical shutter + 5 positions filters wheel + internal guide port	6377	7627
632wsg8	Mechanical shutter + 8 positions filters wheel + internal guide port	6670	7977
SERIE 520	Interline 2 megapixel KAI-2020M sensor Low noise, wide dynamic range, Very fast electronic shutter, Up to 45°C CCD cooling, MaxIm DL and CCDSoft Drivers, Available MaxIm DL or LE camera control and image processing software ,ASCOM-compatible Windows COM API, Linux drivers and API		
520i	Fast electronic shutter	3212	3841
520s	Fast electronic shutter + Mechanical shutter	3309	3958
520ws	Fast electronic shutter + Mechanical shutter + 5 positions filters wheel	3451	4127
520wsg	Fast electronic shutter + Mechanical shutter + 5 positions filters wheel + internal guide port	3792	4535

SERIE 620	Interline 2 megapixel KAI-2020M, Low noise, wide dynamic range, Very fast electronic shutter, Up to 50°C CCD cooling, MaxIm DL and CCDSoft Drivers, PRISM V8 light software ,ASCOM-compatible Windows COM API, Linux drivers and API		
620i	Fast electronic shutter	3602	4308
620s	Fast electronic shutter + Mechanical shutter	3699	4424
620ws	Fast electronic shutter + Mechanical shutter + 5 positions filters wheel	3841	4594
620ws8	Fast electronic shutter + Mechanical shutter + 8 positions filters wheel	4182	5002
620wsg	Fast electronic shutter + Mechanical shutter + 5 positions filters wheel + internal guide port	4182	5002
620wsg8	Fast electronic shutter + Mechanical shutter + 8 positions filters wheel + internal guide port	4475	5352
SERIE 516	Full-frame 1.6 megapixel KAF-1603 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, PRISM Light V8 camera control and image processing software, CCDSoft and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.		
516s	Mechanical shutter	3553	4249
516ws	Mechanical shutter + 5 positions filters wheel	3694	4419
516wsg	Mechanical shutter + 5 positions filters wheel + internal guide port	4036	4827
SERIE 616	Full-frame 1.6 megapixel KAF-1603 sensor Low noise, Low noise, wide dynamic range, 16-bit output, USB 2.0 Up to 50°C CCD cooling, Built-in mechanical shutter, MaxIm DL and CCDSoft Drivers, Prism V8 light software ,ASCOM-compatible Windows COM API, Linux drivers and API, fast download, Prism V8 light offert.		
616s	Mechanical shutter	3846	4599
616ws	Mechanical shutter + 5 position filter wheel	3987	4769
616ws8	Mechanical shutter + 8 position filter wheel	4280	5119
616wsg	Mechanical shutter + 5 positions filters wheel + internal guide port	4329	5177
616wsg8	Mechanical shutter + 8 positions filters wheel + internal guide port	4621	5527
SERIE 504	Full-frame 400.000 pixels KAF-0402 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, PRISM Light V8 camera control and image processing software, CCDSoft and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.		
504s	Mechanical shutter	2821	3374
504ws	Mechanical shutter + 5 positions filters wheel	2963	3543
504wsg	Mechanical shutter + 5 positions filters wheel + internal guide port	3304	3952
SERIE 604	sur demande	nc	nc
	Single-Shot Color Cameras		

583cs	Full-frame 8.3 megapixel KAF-8300 sensor, with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C CCD cooling, Built-in mechanical shutter, MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	2870	3433
583csg	Full-frame 8.3 megapixel KAF-8300 sensor, with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel utilizing standard 1.25" color filters, Integrated Guider Port (IGP), MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	3260	3899
540ci	4.2mp 2048x2048 KAI-04022 sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C C CD cooling, Built-in mechanical shutter, internal 5-position color filter wheel utilizing standard 1.25" color filters, Integrated Guider Port (IGP), MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	3748	4483
540cs	4.2mp 2048x2048 KAI-04022 sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C C CD cooling, Built-in mechanical shutter, internal 5-position color filter wheel utilizing standard 1.25" color filters, Integrated Guider Port (IGP), MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	3846	4599
540csg	4.2mp 2048x2048 KAI-04022 sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C C CD cooling, Built-in mechanical shutter, internal 5-position color filter wheel utilizing standard 1.25" color filters, Integrated Guider Port (IGP), MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	4187	5008
520ci	2 mega pixel KAI-02020 CM sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C C CD cooling, MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	3212	3841
520cs	2 mega pixel KAI-02020 CM sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C C CD cooling, Built-in mechanical shutter, MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API 4.2mp 2048x2048 KAI-04022 sen	3309	3958

520csg	2 mega pixel KAI-02020 CM sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C C CD cooling, Built-in mechanical shutter, internal 5-position color filter wheel, Integrated Guider Port (IGP), MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API	3651	4366
	Accessory		
AC5-CFW	Additional Color Filter Wheel	223	267
AC5-LHX	Liquid Heat Exchanger	194	232
AC5-LHXRP	LHX Recirculating Pump	96	115
AC5-PS12V	QSI 500 Series AC Adapter	155	185
AC5-UV	UV Option w/fused silica window, no coverglass	419	501
	500 Series WSG Upgrades and Accessories	29	34
AC5-WSG-C	QSI 500 Series WSG Upgrade w/C-mount	609	729
AC5-WSG-T	QSI 500 Series WSG Upgrade w/T-mount	609	729
AD5-WSG-C	WSG C-Mount Guide Camera Adapter	125	150
AD5-WSG-T	WSG T-Mount Guide Camera Adapter	125	150
AD5-L-CAP	2.156" x 24tpi Adapter w/ Cap	174	208
ADL-NP2	2" Nosepiece for 2.156" adapter	125	150
AC5-WSCOVER	500 Series WS Cover w/T-mount & Cap	219	262
	500 Series Mounting Adapters	29	34
AD5-C-CAP	C-Mount Adapter Type I w/ Cap	125	150
AD5-CII-CAP	C-Mount Adapter Type II w/ Cap	125	150
AD5-T-CAP	T-Mount Adapter w/ Cap	125	150
	T-mount Threaded Accessories	29	34
ADT-E180	Takahashi Epsilon-180 Adapter	194	232
ADT-NP125	1.25" Nosepiece	77	92
ADT-NP2	2" Nosepiece	77	92
ADT-SLR-C	SLR Lens Adapter - Canon EOS	223	267
ADT-SLR-N	SLR Lens Adapter - Nikon F	223	267