

Tarif QSI

OPTIQUE&VISION

6 avenue de l'esterel 06160 JUAN LES PINS France tel 04 93 61 18 83 fax 04 92 93 09 83

2015-4

Ce tarif peut changer sans préavis

référence		€ HT	€ TTC
SERIE 690	Sony ICX-814 sensor, Low noise, wide dynamic range, 16-bit output, USB 2.0 Up to 45°C CCD cooling, Built-in mechanical shutter ,MaxIm DL and CCDSoft Drivers, ASCOM-compatible Windows COM API, Linux drivers and API.		
690i	very fast electronic shutter	3615	4338
690s	mechanical shutter	3729	4475
690ws	mechanical shutter + filter wheel	3849	4619
690wsg	mechanical shutter + filter wheel + internal guide port for autoguiding	4123	4948
690ws-8	mechanical shutter + filter wheel 8 positions	4123	4948
690wsg8	mechanical shutter + filter wheel 8 positions + internal guide port for autoguiding	4409	5291
SERIE 683	Full-frame 8.3 megapixel KAF-8300 sensor, Low noise, wide dynamic range, 16-bit output, fast USB 2.0, Up to 50°C CCD cooling, Built-in mechanical shutter, MaxIm DL and CCDSoft Driver,ASCOM-compatible Windows COM API, Linux drivers and API, fast download.		
683s	mechanical shutter	3339	4007
683ws	mechanical shutter + 5 positions filter wheel	3574	4288
683ws8	mechanical shutter + 8 positions filter wheel	3859	4631
683wsg	mechanical shutter + 5 positions filter wheel + internal guide port	3859	4631
683wsg8	mechanical shutter + 8 positions filter wheel + internal guide port	4054	4864
SERIE 660	Sony ICX-694 sensor 6.1mp 4.54*4.54 12.48mm*9.98mm 2758*2208 , Low noise, wide dynamic range, 16-bit output, USB 2.0 Up to 45°C CCD cooling, Built-in mechanical shutter ,MaxIm DL and CCDSoft Drivers, ASCOM-compatible Windows COM API, Linux drivers and API.		
660i	Very fast electronic shutter	3396	4076
660s	Very fast electronic shutter + Mechanical shutter	3454	4144
660ws	Very fast electronic shutter + Mechanical shutter + 5 positions filter wheel	3619	4343
660wsg	Very fast elect. shutter + mech. shutter + 5 positions filter wheel + internal guide port	3905	4686

660ws-8	Very fast electronic shutter + Mechanical shutter + 8 positions filter wheel	3905	4686
660wsg-8	Very fast electronic shutter + Mechanical shutter + 5 positions filter wheel + internal guide port	4191	5029
SERIE 640	4.2mp 2048x2048 KAI-04022 sensor, Low noise, wide dynamic range, Very fast electronic shutter, Up to 50°C CCD cooling, MaxIm DL and CCDSoft Drivers, ASCOM-compatible Windows COM API, Linux drivers and API		
640 i	Very fast electronic shutter	4082	4899
640s	Very fast electronic shutter + Mechanical shutter	4196	5036
640ws	Very fast electronic shutter + Mechanical shutter + 5 positions filter wheel	4476	5372
640wsg	Very fast electronic shutter + Mechanical shutter + 8 positions filter wheel	4762	5715
640wsg	Very fast electronic shutter + Mechanical shutter + 5 positions filter wheel + internal guide port	4762	5715
640wsg8	Very fast electronic shutter + Mechanical shutter + 8 positions filter wheel	5002	6003
640 CWS8	KAI 4022 color -Very fast electronic shutter + Mechanical shutter + 8 positions filter wheel	4996	5996
SERIE 632	Full-frame 3.2 megapixel KAF-3200 sensor Low noise, Low noise, wide dynamic range, 16-bit output, Fast USB 2.0 Up to 50°C CCD cooling, Built-in mechanical shutter, MaxIm DL and CCDSoft Drivers, ASCOM-compatible Windows COM API, Linux drivers and API, fast download.		
632s	Mechanical shutter	6482	7779
632ws	Mechanical shutter + 5 position filter wheel	6705	8046
632ws8	Mechanical shutter + 8 position filter wheel	6991	8389
632wsg	Mechanical shutter + 5 positions filters wheel + internal guide port	6991	8389
632wsg8	Mechanical shutter + 8 positions filters wheel + internal guide port	7276	8732
C1-upg	CCD class 1 upgrade	3002	3603
SERIE 620	Interline 2 megapixel KAI-2020M, Low noise, wide dynamic range, Very fast electronic shutter, Up to 50°C CCD cooling, MaxIm DL and CCDSoft Drivers, ASCOM-compatible Windows COM API, Linux drivers and API		
620i	Fast electronic shutter	3911	4693
620s	Fast electronic shutter + Mechanical shutter	4025	4830
620ws	Fast electronic shutter + Mechanical shutter + 5 positions filters wheel	4305	5166
620ws8	Fast electronic shutter + Mechanical shutter + 8 positions filters wheel	4534	5440
620wsg	Fast electronic shutter + Mechanical shutter + 5 positions filters wheel + internal guide port	4534	5440
620wsg8	Fast electronic shutter + Mechanical shutter + 8 positions filters wheel + internal guide port	4819	5783
SERIE 616	Full-frame 1.6 megapixel KAF-1603 sensor Low noise, Low noise, wide dynamic range, 16-bit output, USB 2.0 Up to 50°C CCD cooling, Built-in mechanical shutter, MaxIm DL and CCDSoft Drivers, ASCOM-compatible Windows COM API, Linux drivers and API, fast download.		
616s	Mechanical shutter	4425	5310
616ws	Mechanical shutter + 5 position filter wheel	4591	5509
616ws8	Mechanical shutter + 8 position filter wheel	4934	5920

616wsg	Mechanical shutter + 5 positions filters wheel + internal guide port	4991	5989
616wsg8	Mechanical shutter + 8 positions filters wheel + internal guide port	5334	6400