

# www.OVISION.com

## tarif QSI

OPTIQUE&VISION

6 avenue de l'esterel 06160 JUAN LES PINS France tel 04 93 61 18 83 fax 04 92 93 09 83

au 17/05/2010

référence	description	€ HT	€ TTC
583s	Full-frame 8.3 megapixel KAF-8300 sensor, Low noise, wide dynamic range, 16-bit output, USB 2.0 Up to 45°C CC D cooling, Built-in mechanical shutter ,MaxIm DL and CCDSoft Drivers, Available MaxIm DL or LE camera control and image processing software ,ASCOM-compatible Windows COM API, Linux drivers and API	2685.90	3212
583ws	Full-frame 8.3 megapixel KAF-8300 sensor, Low noise, wide dynamic range, 16-bit output, USB 2.0 Up to 45°C CC D cooling, Built-in mechanical shutter, Internal 5-position color filter wheel, MaxIm DL and CCDSoft Drivers, Available MaxIm DL or LE camera control and image processing software ,ASCOM-compatible Windows COM API, Linux drivers and API	2986.80	3572
583wsg	Full-frame 8.3 megapixel KAF-8300 sensor, Low noise, wide dynamic range, 16-bit output, USB 2.0 Up to 45°C CC D cooling, Built-in mechanical shutter, Internal 5-position color filter wheel, integrated Off axis guide port, MaxIm DL and CCDSoft Drivers, Available MaxIm DL or LE camera control and image processing software ,ASCOM-compatible Windows COM API, Linux drivers and API	3394.80	4060
540i	4.2mp 2048x2048 KAI-04022 sensor, Low noise, wide dynamic range, Very fast electronic shutter, Up to 45°C CCD cooling, MaxIm DL and CCDSoft Drivers, Available MaxIm DL or LE camera control and image processing software ,ASCOM-compatible Windows COM API, Linux drivers and API	3705.90	4432
540s	4.2mp 2048x2048 KAI-04022 sensor, Low noise, wide dynamic range, Very fast electronic shutter, Up to 45°C CCD cooling, mechanical shutter, MaxIm DL and CCDSoft Drivers, Available MaxIm DL or LE camera control and image processing software ,ASCOM-compatible Windows COM API, Linux drivers and API	3960.90	4737
540ws	4.2mp 2048x2048 KAI-04022 sensor, Low noise, wide dynamic range, Very fast electronic shutter, Up to 45°C CCD cooling, mechanical shutter, internal 5-position color filter wheel, MaxIm DL and CCDSoft Drivers, Available MaxIm DL or LE camera control and image processing software ,ASCOM-compatible Windows COM API, Linux drivers and API	4414.80	5280
540wsg	4.2mp 2048x2048 KAI-04022 sensor, Low noise, wide dynamic range, Very fast electronic shutter, Up to 45°C CCD cooling, mechanical shutter, internal 5-position color filter wheel, integral Off-Axis Guider (OAG), MaxIm DL and CCDSoft Drivers, Available MaxIm DL or LE camera control and image processing software ,ASCOM-compatible Windows COM API, Linux drivers and API	4771.80	5707

532s	Full-frame 3.2 megapixel KAF-3200 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, MaxIm LE camera control and image processing software, CCDSOFT and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	5490.90	6567
532ws	Full-frame 3.2 megapixel KAF-3200 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel, MaxIm LE camera control and image processing software, CCDSOFT and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	5944.80	7110
532wsg	Full-frame 3.2 megapixel KAF-3200 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel, integral Off-Axis Guider (OAG), MaxIm LE camera control and image processing software, CCDSOFT and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	6301.80	7537
<b>Class 1 upgrade</b>		192.00	NC
520i	Interline 2 megapixel KAI-2020M sensor Low noise, wide dynamic range, Very fast electronic shutter, Up to 45°C CCD cooling, MaxIm DL and CCDSOFT Drivers, Available MaxIm DL or LE camera control and image processing software, ASCOM-compatible Windows COM API, Linux drivers and API	2889.90	3456
520s	Interline 2 megapixel KAI-2020M sensor Low noise, wide dynamic range, Very fast electronic shutter, Up to 45°C CCD cooling, mechanical shutter, MaxIm DL and CCDSOFT Drivers, Available MaxIm DL or LE camera control and image processing software, ASCOM-compatible Windows COM API, Linux drivers and API	3144.90	3761
520ws	Interline 2 megapixel KAI-2020M sensor Low noise, wide dynamic range, Very fast electronic shutter, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel, MaxIm LE camera control and image processing software, CCDSOFT and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	3598.80	4304
520wsg	Interline 2 megapixel KAI-2020M sensor Low noise, wide dynamic range, Very fast electronic shutter, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel, integral Off-Axis Guider (OAG), MaxIm LE camera control and image processing software, CCDSOFT and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	3955.80	4731
516s	Full-frame 1.6 megapixel KAF-1603 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, MaxIm LE camera control and image processing software, CCDSOFT and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	3705.90	4432
516ws	Full-frame 1.6 megapixel KAF-1603 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel, MaxIm LE camera control and image processing software, CCDSOFT and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	4159.80	4975
516wsg	Full-frame 1.6 megapixel KAF-1603 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel, integral Off-Axis Guider (OAG), MaxIm LE camera control and image processing software, CCDSOFT and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	4516.80	5402

504s	Full-frame 400.000 pixels KAF-0402 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, MaxIm LE camera control and image processing software, CCDSoft and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	2481.90	2968
504ws	Full-frame 400.000 pixel KAF-0402 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel, MaxIm LE camera control and image processing software, CCDSoft and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	2935.80	3511
504wsg	Full-frame 400.000 pixel KAF-0402 sensor Low noise, wide dynamic range, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel, integral Off-Axis Guider (OAG), MaxIm LE camera control and image processing software, CCDSoft and MaxIm DL Drivers ASCOM-compatible Windows API, Linux drivers and API.	3292.80	3938
	<b>Class 1 upgrade</b>	192.00	NC
	<b>Single-Shot Color Cameras</b>		
583cs	Full-frame 8.3 megapixel KAF-8300 sensor, with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C CCD cooling, Built-in mechanical shutter, MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	3450.90	4127
583csg	Full-frame 8.3 megapixel KAF-8300 sensor, with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel utilizing standard 1.25" color filters, Integrated Guider Port (IGP), MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	3909.90	4676
540ci	4.2mp 2048x2048 KAI-04022 sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel utilizing standard 1.25" color filters, Integrated Guider Port (IGP), MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	3705.90	4432
540cs	4.2mp 2048x2048 KAI-04022 sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel utilizing standard 1.25" color filters, Integrated Guider Port (IGP), MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	3960.90	4737
540csg	4.2mp 2048x2048 KAI-04022 sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C CCD cooling, Built-in mechanical shutter, internal 5-position color filter wheel utilizing standard 1.25" color filters, Integrated Guider Port (IGP), MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	4419.90	5286
520ci	2 mega pixel KAI-02020 CM sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C CCD cooling, MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API	2889.90	3456

520cs	2 mega pixel KAI-02020 CM sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C C CD cooling, Built-in mechanical shutter, MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API, Linux drivers and API H 4.2mp 2048x2048 KAI-04022 sen	3144.90	3761
520csg	2 mega pixel KAI-02020 CM sensor , with integral RGB Bayer Color Filter Array, Single-Shot color imaging, Low noise, wide dynamic range, 16-bit output, USB 2.0, Up to 45°C C CD cooling, Built-in mechanical shutter, internal 5-position color filter wheel, Integrated Guider Port (IGP), MaxIm DL and CCDSoft Drivers, Macintosh support using Nebulosity, ASCOM-compatible Windows API	3603.90	4310
<b>ACCESSORY</b>			
AC5-CFW	Carroussel pour filtres vissants 31.75 mecanique	214.26	256
AC5-CFW un	carroussel pour filtres 31 mm non vissants	255.12	305
AC5-LHX	Liquid Heat Exchanger	187.61	224
AC5-LHXRP	LHX Recirculating Pump	98.79	118
AC5-PS12V	QSI 500 Series AC Adapter	152.08	182
AC5-UV	UV Option w/fused silica window, no coverglass	392.80	470
<b>500 Series WSG Upgrades and Accessories</b>			
AC5-WSG-C	QSI 500 Series WSG Upgrade w/C-mount	566.01	677
AC5-WSG-T	QSI 500 Series WSG Upgrade w/T-mount	566.01	677
AD5-WSG-C	WSG C-Mount Guide Camera Adapter	125.44	150
AD5-WSG-T	WSG T-Mount Guide Camera Adapter	125.44	150
AD5-L-CAP	2.156" x 24tpi Adapter w/ Cap	169.85	203
ADL-NP2	2" Nosepiece for 2.156" adapter	125.44	150
AC5-WSCOVER	500 Series WS Cover w/T-mount & Cap	210.71	252
<b>500 Series Mounting Adapters</b>			
AD5-C-CAP	C-Mount Adapter Type I w/ Cap	125.44	150
AD5-CII-CAP	C-Mount Adapter Type II w/ Cap	125.44	150
AD5-T-CAP	T-Mount Adapter w/ Cap	125.44	150
	T-mount Threaded Accessories	0.00	0
ADT-E180	Takahashi Epsilon-180 Adapter	187.61	224
ADT-NP125	1.25" Nosepiece	81.02	97
ADT-NP2	2" Nosepiece	81.02	97
ADT-SLR-C	SLR Lens Adapter - Canon EOS	214.26	256